

NEW PROFESSIONAL 2 BOTTLE WINE SERVING SYSTEM WHICH HOLDS THE BASIC FUNCTIONALITIES OF THE ENOMATIC® TECHNOLOGY IN A COMPACT AND ELEGANT DESIGN. USER-FRIENDLY “PLUG & PLAY” INSTALLATION. PERFECT FOR HOME USE, TOO.



enoliving

- Available model: enoliving 2 RT (2 bottles).
- Wine temperature: Room Temperature.
- Installation: “plug & play”.
- Gas supply:
 - food-grade argon gas (E938) disposable canister
 - optional: food-grade nitrogen (E941) or argon (E938) external gas cylinder
- Servings: 1 configurable volume (preset volume or free serving on pressure).
- Finishes: stainless steel with black or white Baydur sides and mirror bottle chamber.
- Lighting: double LED.
- Gas depletion alarm: gas cylinder depletion with LED flash alert.
- Bottle positioning: gas strut lifter with curve bottle spacer allowing the correct bottle positioning.
- Accessories upon request:
 - 0.95 lt. disposable argon (E938) gas canister (supplies approx. 90 bottles)
 - inlet adapter for external gas cylinder
- Energy consumption: 58.4 kWh/year (average 7 servings of 60 cc per day).



model	L	H	D	weight	electrical requirements
enoliving 2 RT	24.3 cm (9.6")	58.4 cm (23")	27.7 cm (10.91")	15 kg (33 lbs)	100-240 V 50-60 Hz 25 W
enoliving 2 RT	24.3 cm (9.6")	58.4 cm (23")	27.7 cm (10.91")	15 kg (33 lbs)	115 V 60 Hz 25 W